

Model	Rated flow		Rated head (m)	NPSH (m)	Efficiency%	Power		Weight (kg)
	(L/min)	(m³/h)				HP	KW	
QBF40-25-140	100	6	25	40/25	<1.2	3	2.2	85
QBF40-25-170	100	6	35	40/25	<1.2	4	3	90
QBF40-25-180	100	6	40	40/25	<1.2	5.5	4	93
QBF40-25-200	100	6	50	40/25	<1.2	7.5	5.5	160
QBF50-32-130	208	12.5	20	50/32	<1.2	3	2.2	95
QBF50-32-160	208	12.5	32	50/32	<1.2	5.5	4	105
QBF50-40-160	250	15	30	50/40	<1.2	7.5	5.5	140
QBF50-40-180	250	15	40	50/40	<1.2	7.5	5.5	140
QBF50-32-200	208	12.5	50	50/32	<1.2	10	7.5	170
QBF50-32-250	208	12.5	80	50/32	<1.2	20	15	280
QBF65-50-130	500	30	20	65/50	<1.2	5.5	4	130
QBF65-50-160	500	30	30	65/50	<1.2	7.5	5.5	135
QBF65-50-170	500	30	35	65/50	<1.2	10	7.5	145
QBF65-40-200	416	25	50	65/40	<1.2	15	11	300
QBF65-40-250	416	25	80	65/40	<1.2	25	18.5	320
QBF80-65-130	1000	60	20	80/65	<1.2	10	7.5	280
QBF80-65-170	1000	60	35	80/65	<1.2	15	11	300
QBF80-50-180	833	50	40	80/50	<1.2	20	15	330
QBF80-50-200	833	50	50	80/50	<1.2	20	15	335
QBF80-50-250	833	50	80	80/50	<1.2	40	30	390
QBF100-80-130	1666	100	20	100/80	<1.2	20	15	410
QBF100-80-160	1666	100	32	100/80	<1.2	25	18.5	415
QBF100-65-200	1666	100	50	100/65	<1.2	40	30	485
QBF125-100-130	2666	160	20	125/100	<1.2	40	30	630
QBF125-100-160	2666	160	32	125/100	<1.2	50	37	680
QBF125-100-200	2666	160	40	125/100	<1.2	60	45	730
QBF150-125-250	3333	200	20	150/125	<1.2	30	22/4P	490
QBF150-125-315	3333	200	30	150/125	<1.2	50	37/4P	720

● Medium temperature: -20 ℃~+100 ℃, medium specific gravity: 1-2, working environment temperature: -5 ℃~+50 ℃, maximum operating altitude: 2000m, maximum working pressure: 10Bar. Medium temperature: -20 ℃~+100 ℃, medium specific gravity: 1-2, working environment temperature: -5 ℃~+50 ℃, maximum operating altitude: 2000m, maximum working pressure: 10Bar.